



# GSM Modem proCOM<sup>®</sup>

**Modem to extend the proControl<sup>®</sup> 2 unit for the remote transmission of data via SMS**

## General Features

- Ready to plug system
- Configuration via the menu “communication” of the proControl<sup>®</sup> 2 unit
- Transmission of messages in the selected menu language
- Error remote acknowledgement via SMS
- Data transmission to 3 target phone numbers
- Retrieve data via all registered phone numbers

By sending SMS text messages “...” to the modem, the following information can be retrieved from the proControl<sup>®</sup> 2 unit:

- “Info” → commissioning data
- “Error” → error logbook entries
- “Time” → cumulative run-times
- “Week” → weekly run-times

## Technical Data

- Dimension (L x W x TH): 90 x 150 x 25 mm
- Temperature range: 0°C ... +70°C (excluding batteries)
- Power supply: 24VDC
- Connections: +24VDC, Ground, FME-Antenna socket, RS-232 connector
- Batteries: 2 x AA Mignon NiMH, 1.2 V, 2100 mAh, charging time approx. 20 h
- Transmission range: Quad band 850/900/1800/1900Mhz
- Accessories: Antenna with FME-connector and 2.5 m cable



GSM Modem proCOM<sup>®</sup> slide board